

MAXIFORST

max. 60 cm Ø 300-500 HP

Powerful mulcher for uncompromising work under the toughest conditions

MAXIFORST takes on the most demanding jobs and handles every challenge. The particularly powerful machine and its powerful transmission with double drive mulches wood up to 60 cm in diameter.

This is the ideal machine for Land Clearing and ROW Maintenance. Whether it is the cleaning up after harvesting timber, maintenance of power lines or cleaning up after hurricanes or forest fires. The integrated cooler ensures a constant performance. Its special strength combined with robust material properties make MAXIFORST a strong partner for large projects.

Standard version and specifications

- > Mulches wood up to 60 cm [24"] Ø
- > Working speed 0-5 km/h
- > 3 point rear linkage cat. 3 & 4 central fixed
- > 1000 rpm gearbox with freewheel, integrated cooling
- > ADAM™ alignment system
- > Dual side belt transmission
- > Hydraulically operated hood
- > Reinforced skids, adjustable in height
- > Front- and rear protection with chains
- > Tempered counter cutters
- > Standard rotor with fixed hammers MINI DUO with 2 tungsten carbide inserts

Optional configuration and accessories

- > Fixed hammers with tungsten carbide inserts MONO HIT V-LOCK
- > Hydraulic top link
- > Fluid turbo coupling M-TURBO
- > Hydraulic guard frame (various models available)
- > Rakes on rear hood



[YouTube www.youtube.com/seppimulcher](https://www.youtube.com/seppimulcher)

Specifications · MAXIFORST	Nominal Tractor Power 300-500 HP	
Working width	250 cm [98"]	300 cm [118"]
Overall width	300 cm [118"]	350 cm [118"]
Depth	150 cm [59"]	150 cm [59"]
Height	150 cm [59"]	150 cm [59"]
Weight (base value w/o options)	4.330 kg [9550lb]	4.960 kg [10930lb]
Belts	2x5	2x5
Fixed hammers · MINI DUO	54	66
Fixed hammers · MONO TIP + lateral	77+6	91+6

Tools



Fixed hammer
MINI-DUO




Fixed hammer
MONO HIT V-LOCK



Lateral hammer
V-LOCK EXTREME

ADAM™ alignment system



ADAM™ alignment system (standard feature)

Tilting of the mulcher by gear tracking with PTO shaft alignment. With the W-shaped angles the range of motion increases and the mulcher can be moved up- and downwards even higher. This angular adjustment protects the PTO shaft and the input shaft even at high loads and supports an ideal adaptation to the conditions of the roads. Advantages: longer service life of PTO and input-shaft, even deeper digging, working with an alignment system is easier and faster.

www.seppi.com/en/adam
video ADAM™



MAXIFORST

High performance forestry tiller with a large rotor diameter, a reinforced chassis and additional material deflectors. The machine is completely covered and protected; easy access due to the hatch for service and maintenance.

COOLER
Powerful transmission with double belt drive - integrated cooling

Fluid turbo coupling M-TURBO for a slow start and to protect the tractor (option)

Belt protection with material deflector

Adjustable in height skirts, reinforced with replaceable hard metal plate

HEAVY CHAINS protect tractor and driver

Guard frame for felling operations and to protect the tractor (option)

HELIX ROTOR
CARBIDE

COUNTER CUTTERS
WEARPLATE

Exposed position of the rotor for an easy grip to the material

Rotor with fixed hammers, for mulching wood and soil cultivation

Reinforced chassis with replaceable wear-resistant steel plates
5 rows of tempered counter cutters for a perfect mulching result