

WBS fh

130-250 HP

Ø max. 11 cm [4.3 inch]

Strong heavy duty flail mulcher with innovative reversible linkage

The WBS series machines mulch grass, vegetation and prunings up to 11 cm [4.3"] in diameter. The adjustable rear hood allows you to alter the degree of mulching.

The **WBS fh** is characterized by an innovative, pyramid-shaped 3-point linkage, suitable for front and rear attachment. The top link connection provides high stability and is easily reversed to allow front or rear mount to be achieved without heavy lifting.

Standard version and characteristics

- > Mulches grass and brush up to 11 cm [4.3"]Ø
- > Working speed 3-10 km/h
- > 3 point linkage cat. 2 reversible
- > Linear hydraulic side shift
- > 1000 rpm gearbox with freewheel and through shaft
- > Belt transmission
- > Adjustable rear hood with rubber protection
- > Front protection with chains
- > Support roller 193 mm Ø
- > Rotor with SMO flails

Optional configuration and accessories

- > 540 rpm gearbox
- > Front attachment
- > Additional front rubber flap
- > Rake hood complete with rakes
- > Fine shred kit



www.youtube.com/seppimulcher

Tools



Specifications · WBS fh				Nominal tractor power 130-250 HP				
			225 [89]	250 [98]	275 [108]	300 [118]	350 [138]	
Working width	cm [inch]							
Side shift from	max to the left	L R cm [inch]	133 92 [52 36]	158 92 [62 36]	171 104 [67 41]	183 117 [72 46]	208 142 [82 56]	
	max to the right	L R cm [inch]	66 159 [26 63]	91 159 [36 63]	103 172 [41 68]	116 184 [46 72]	141 209 [56 82]	
Overall width	cm [inch]		245 [96]	270 [106]	295 [116]	320 [126]	370 [146]	
Depth	cm [inch]		140 [55]	140 [55]	140 [55]	140 [55]	140 [55]	
Height	cm [inch]		125 [49]	125 [49]	125 [49]	125 [49]	125 [49]	
Weight · base value	kg		1.480 [3,260]	1.540 [3,400]	1.650 [3,640]	1.700 [3,750]	1.880 [4,150]	
Belts	Anzahl		5	5	5	5	5	
Flails	Anzahl		24	26	28	32	36	

WBS fh · features

Robust reinforced chassis made of high tensile steel.

S420

Hydraulic side shift:
linear up to 68 cm [27"]

Powerful gearbox with
freewheel and through
shaft for front and rear
mount and reverse drive
FR
FRONTREAR

Innovative, pyramid-shaped 3-point
linkage with high stability, suitable
for front and rear attachment -
The weight is close to the tractor

2 options of choice: rear hood with
rakes for better collection of prunings
and branches or Fine Shred KIT with 2
additional rows of counter cutters

Adjustable hood
to set the degree of
mulching
M-FLAP

Strong roller with double tapered
bearing unit for a long life,
the large diameter improves
mulching on uneven ground.

Due to the close position of the roller
to the rotor, the rotating flails clean
the roller, and the cut material is evenly
distributed over the top.

Rotor with SMW flails
Low power consumption at
maximum throughput with
helix rotor technology
HELIX ROTOR

Replaceable tempered counter
cutters inside the casing provide
a perfect result when mulching.
**2 COUNTER
CUTTERS**