

WBS

130-250 HP

∅ max. 11 cm [4.3 inch]

Strong heavy duty flail mulcher with reversible linkage

WBS series machines mulch grass, vegetation and prunings up to 11 cm [4.3"] in diameter. The adjustable rear hood allows you to alter the degree of mulching.

The **WBS** has a central 3-point linkage. The mulcher is reversible and can be driven in both direction - front and rear.

You can get this model also with motor - ready to go with a hydraulic track loader!


Standard version and characteristics

- > Mulches grass and brush up to 11 cm [4.3"]∅
- > Working speed 3-10 km/h
- > 3 point linkage cat. 2 reversible
- > 1000 rpm gearbox with freewheel and through shaft
- > Belt transmission
- > Adjustable rear hood with rubber protection
- > Front protection with chains
- > Support roller 193 mm ∅
- > Rotor with SMO flails

Optional configuration and accessories

- > 540 rpm gearbox
- > Additional 3-point linkage
- > Front attachment
- > Additional front rubber flap
- > Rake hood complete with rakes
- > Fine shred kit
- > Linkage for for hydraulic track loader / slope groomer and transmission with 80 cm³ motor (available for models 225, 300, 350)



 www.youtube.com/seppimulcher

Tools



Specifications · WBS		Nominal tractor power 130-250 HP				
		225 [89]	250 [98]	275 [108]	300 [118]	350 [138]
Working width	cm [inch]	225 [89]	250 [98]	275 [108]	300 [118]	350 [138]
Overall width	cm [inch]	245 [96]	270 [106]	295 [116]	320 [126]	370 [146]
Depth	cm [inch]	140 [55]	140 [55]	140 [55]	140 [55]	140 [55]
Height	cm [inch]	125 [49]	125 [49]	125 [49]	125 [49]	125 [49]
Weight · base value	kg [lb]	1.210 [2,670]	1.270 [2,800]	1.370 [3,020]	1.420 [3,130]	1.600 [3,530]
Belts	qty	5	5	5	5	5
Flails	qty	24	26	28	32	36


WBS · features

Robust reinforced chassis made of high tensile steel.


S420




Powerful gearbox with freewheel and through shaft for front and rear mount and reverse drive




Optional rear hood with rakes for better collection of prunings and branches



Optional fine shred kit - hood with rakes and additional rows of counter cutters




Adjustable hood to set the degree of mulching




Rotor with SMW flails
Low power consumption at maximum throughput with helix rotor technology



Strong roller with double tapered bearing unit for a long life, the large diameter improves mulching on uneven ground.



Due to the close position of the roller to the rotor, the rotating flails clean the roller, and the cut material is evenly distributed over the top.



Replaceable tempered counter cutters inside the casing provide a perfect result when mulching.

